PRO-C[™]

Simple programming and flexible station expansion make Pro-C the professional's choice for residential and light commercial systems.

KEY BENEFITS

- Number of stations:
 - Modular Pro-C
 - $\,\circ\,$ Conventional wiring from 4 to 23 stations
 - Hybrid EZ Decoder option up to 32 total stations (28 stations max. if two-wire only)
 - Fixed PCC with 6- and 12-station options
- 3 independent irrigation programs (4 start times each) allow for customised scheduling
- 1 sensor input available for use with Solar Sync[™] or any Clik sensors
- 1 P/MV output for pump start relay and master valve activation
- Add a Solar Sync[™] Sensor to save water based on local weather conditions
- Easy Retrieve[™] Memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck[™] Technology provides simple diagnostics of faulty field wiring

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: IP44 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years

PRO-C - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4							
1 Model	2	Transformer	3	Indoor/Outdoor	4	Options	
PC-4 = 4-station base module controller	00 = 120 VAC 01 = 230 VAC		(blank) = Outdoor model (internal transformer) i = Indoor model (plug-in transformer)		(blank) = No option E = 230 VAC with European connections, no plug		
PCC-6 = 6-station							
PCC-12 = 12-station					A = Au (ou int	= 230 VAC with stralian connections utdoor models have ernal transformer th plug)	

Examples:

PC-400 = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet **PCC-601i-E** = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet

PCC-1200 = Fixed 12-station outdoor controller, internal 120 VAC transformer, and plastic cabinet

PC-SERIES STATION EXPANSION

Modules	Description			
PCM-300	3-station plug-in module			
PCM-900	9-station plug-in module			
PCM-1600	16-station plug-in module			
PC-DM	EZ Decoder output module			
PCM-1600-KIT	Upgrade kit for 16-station plug-in module			
PC-DM-KIT	Upgrade kit for EZ Decoder output module			



Plastic Indoor Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm



Plastic Outdoor Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm

Compatible with:





Smart WaterMark Recognised as a responsible water-saving tool when used with a Solar Sync Sensor

RESIDENTIAL & COMMERCIAL IRRIGATION | Built on Innovation[®]